

**QUICK REFERENCE GUIDE**

<b>Series</b>	<b>Groups</b>	<b>Width</b>	<b>Height</b>	<b>Depth</b>	<b>Shipping Weight</b>	<b>Net Weight</b>	<b>Volts</b>	<b>Watts</b>	<b>Amps</b>	<b>Boiler Ca</b>	<b>Plug Requirement</b>	
<i>Caffetteria Italiana</i>		21.5	29.7	23.6	221	202.5	220	6000	30	3.5	<i>Nema L6-30 Twist</i>	
<i>Master Cappuccino</i>	1	26.8	27.6	20.1	198	165	220	2600	11.8	3.5 lt	<i>Nema 6-20</i>	
<i>Master Coffee</i>	1	16.5	27.6	20.1	132	121	220	2400	10.9	3.5 lt	<i>Nema 6-20</i>	
<i>Master Cupwarmer</i>		11.8	25.2	20.1	48	44	220	230	1		<i>Nema 6-20</i>	
<i>Microbar</i>	1	12.25	18.37	21	73	66	110	1500	15	0.7 x 2	<i>Nema 5-15</i>	
<i>Microbar</i>	1	12.25	18.37	21	73	66	220	2000	10	0.7 x 2	<i>Nema 6-20</i>	
<i>Program VIP RAISED</i>	2	30.1	18.9	20.1	172	158	220	3000	13.6	13 lt	<i>Nema 6-20</i>	
	3	38.4	18.9	20.1	198	176	220	5000	22.7	20 lt	<i>Nema L6-30 Twist</i>	
	4	46.7	18.9	20.1	231	198	220	5000	22.7	27 lt	<i>Nema L6-30 Twist</i>	
<i>Aurelia</i>	2	31	21	21.5	176	136	220	4500	20	11 lt	<i>Nema L6-30 Twist</i>	
	3	41	21	21.5	216	194	220	5000	22.7	17 lt	<i>Nema L6-30 Twist</i>	
	4	49	21	21.5	264	229	220	5000	22.7	22 lt	<i>Nema L6-30 Twist</i>	
<i>Appia V/S</i>	1	9	12.5	20.5	106	92.6	115	1500		5 lt	<i>Nema 5-15</i>	
	2	30 7/8	20 13/16	###	143	133	220	3000	14	11 lt	<i>Nema 6-20</i>	
	3	39 7/8	20 13/16	###	143	133	220	5000	23	15 lt	<i>Nema L6-30 Twist</i>	
<i>Mac 2000 V/S</i>	1	14.6	17.3	20.7	110	99	110	1500	13.6	4.8 lt	<i>Nema 6-20</i>	
	2	30.9	17.3	20.7	167	154	220	3000	13.6	10 lt	<i>Nema 6-20</i>	
	3	39.2	17.3	20.7	194	172	220	5000	22.7	16 lt	<i>Nema L6-30 Twist</i>	
<i>not available in semi-auto</i>	4	47.2	17.3	20.7	224	194	220	5000	22.7	22 lt	<i>Nema L6-30 Twist</i>	
<i>Premier Maxi V/S</i>	2	25	18.5	20.5	123	110	220	2700	12.3	5 lt	<i>Nema 6-20</i>	
	3	34.1	18.5	20.5	165	152	220	4500	20.5	14 lt	<i>Nema L6-30 Twist</i>	
<i>Oscar P/O Direct Conn</i>	1	12	15.8	15.8	39	31	110	1200	15	2.5 lt	<i>Nema 5-15</i>	
<i>Jazz</i>	1	9	14.6	13	31	27	110	1500	15	0.7 lt	<i>Nema 5-15</i>	
<i>MDX grinder</i>		7.5	23	14.2	33	23	110	290	2.6		<i>Nema 5-15</i>	
<i>MDXA grinder</i>		7.5	23	14.2	33	23	110	290	2.6		<i>Nema 5-15</i>	
<i>MCD65 bulk grinder</i>		7.9	26	10.6	33	24	110	250	2.3		<i>Nema 5-15</i>	
<i>MCF grinder</i>		4.1	12.2	7.9		12	110	150	1.5		<i>Nema 5-15</i>	
<i>Grinta Grinder</i>		6	17	9	12	8	110	220	2		<i>Nema 5-15</i>	
<i>Eureka</i>											<i>Nema 5-15</i>	
<i>P1L</i>		15	11.25	17.5	55	48	110	1500	15		<i>Nema 5-15</i>	
<i>P2L</i>		20.5	11.25	17.5	75	65	220	3000	20		<i>Nema 6-20</i>	
<i>Kiara 5</i>		19	30	20	84		220	3150	20		<i>Nema 6-20</i>	
<i>Kiara 6</i>		23	32	25	141		220	3750	20		<i>Nema 6-20</i>	
<i>Cristal Horizon granita</i>	1	7.9	33.1	18.9	73	66	110	530	15	4.8	<i>Nema 5-15</i>	
	2	15.7	33.1	18.9	136	128	110	850	15	7.7	<i>Nema 5-15</i>	
	3	23.6	33.1	18.9	172	163	110	1100	15	10	<i>Nema 5-15</i>	
<i>Milk Cooler</i>		9	12.5	14.5								
<i>Water Requirements</i>												
	<i>3/8"dedicated cold water line with shut off valve and compression fitting</i>											

**QUICK REFERENCE GUIDE**

	<i>if water supply pressure exceeds 5 Bar (70 psi) a pressure reducing regulator must be installed by plumber</i>									
	<i>flow rates</i>									
		<i>1-group-35 GPH</i>		<i>3-group-75 GPH</i>						
		<i>2-group-60 GPH</i>		<i>4-group-100 GPH</i>						
<b>Drain Requirements</b>										
	<i>open gravity drain of minimum 1.25 inch I.D, within 3 feet of machine</i>									